

Alcotest 6000

Workplace Breathalyser



Choose the device from the world market leader.



The Alcotest 6000 breathalyser allows professional users to test with speed and precision. Featuring a 12 monthly calibration interval and data logging + download capability, the measuring technology of this small and user-friendly portable alcohol testing device.

The device is ready to use within seconds. This means that you can perform an active test on a subject at any time. It is also possible to measure alcohol in the ambient air (passive), in which case a mouthpiece isn't required.

All functions required for a measurement are activated with the convenient blue OK button, while two menu buttons are used for navigation.

**Active (Blow)
Testing Mode**

**Passive (Talk)
Testing Mode**

**AS 3547:2019
Certified**

Fuel Cell Technology

**12 Month
Calibration Interval**

Made In Germany

Easy To Operate



**Buy Online
Now!**



Alcotest 6000

Workplace Breathalyser

Alcotest Hygiene Plus

Hygiene is an increasingly important part of our everyday lives. Alcotest breath-alcohol detection devices use non-invasive measuring technologies with a high degree of hygiene – for the user as well as the test subject – thanks to the following features:

During testing, the exhaled air is directed past rather than through the device.

There is a 90° angle between the user and the test subject during testing.

Disposable mouthpiece is individually packaged and a safe, hygienic distance between user and test subject is maintained during testing. The spacer prevents direct contact between lips and device.

The mouthpiece is easy to remove.

The tried and tested electro-chemical Dräger sensor in the Alcotest 6000 is distinguished by its very fast response times and a long service life. It operates with extreme precision and reliability. The analysis is reliable even at temperatures of -5 to +50 °C. The sensor also delivers reliable results quickly in case of a high alcohol content, for both active and passive measurements.

An intuitive operation of the device is an important aspect for ease of use and smooth breath testing procedures.

All measurement functions can be operated with just one button to make it easier for you to perform the test. The large back-lit display is easy to understand due to its full-text messages which guide you securely through the alcohol test. An LED and audible signal complement the display and indicate the end of a measurement process. Two menu buttons are used to navigate through the menu, enabling you to perform functions such as reviewing the last test results.

| | |
|-----------------------|---------------------------------|
| Measuring Principle | Electrochemical Fuel Cell |
| Measuring Range | 0.000 - 0.500 g/210L |
| Ready For Use | 2 seconds after switching on |
| Operating Temperature | -5 to +50°C |
| Data Storage | 500 Results with Date/Time & ID |
| Power Supply | 1 x CR123-A Battery |
| Calibration Interval | 12 Months |
| Dimensions | 50/60 x 141 x 31mm |
| Weight | 150 grams |

(03) 9125 4520

drugtestwarehouse.com.au

sales@drugtestwarehouse.com.au



**Buy Online
Now!**